


REV:	DESCRIPTION	BY	DATE
V1.0	New issue	SD-02	2017-10-10

NO	Symbol
1	VSS
2	VDD
3	V0
4	/RST
5	/RS
6	/RW
7	E1
8	E2
9	PSB
10	DB0
11	DB1
12	DB2
13	DB3
14	DB4
15	DB5
16	DB6
17	DB7
18	LEDA
19	LEDK
20	VOUT(NC)

- NOTES :
- | | |
|---|---|
| 1. LCD TYPE: | STN-Blue, Negative Transmissive |
| 2. OPERATING VOLTAGE: | VDD=5.0V, Vop=6.0V |
| 3. VIEWING DIRECTION: | 6 O'CLOCK |
| 4. DRIVE METHOD: | 1/32 Duty, 1/6 Bias |
| 5. OPERATING TEMP: | -20°C TO +70°C |
| 6. STORAGE TEMP: | -30°C TO +80°C |
| 7. CONNECTOR TAPE: | Zebra |
| 8. DRIVER IC: | AIP31020 or Equivalent |
| 9. BACKLIGHT: | 5 PCS LED White (Side) |
| 10. ALL sub-parts and materials of the parts, | must comply with the RoHS instructions of EU. |

 SINDA DISPLAY TECHNOLOGY CO., LTD.				
SHEET: 1 of 1		MODEL NUMBER : SDGB19264-04	VERSION: 1.0	UNITS: MM
APPROVALS	DATE	GENERAL TOL: ± 0.2		
DWN	SD-02	DO NOT SCALE THIS DRAWING.		
CHK				
APP	SD-11			
		www.sindadisplay.com		SCALE: 1:1